

# PRODUCT SHEET

<b>ITEM'S NAME</b>	DALIA COMFORT DC/A3G
<b>ITEM'S CODE</b>	

DATA	U.M.	VALUE
Width	cm	74
Height	cm	116
Depth	cm	72
Seat height	cm	43-56
Armrest height (25 cm from the front)	cm	58
Shell weight without fabric	kg	11.9
Total weight without fabric	kg	16.8
Hole spacing 6MA	mm	140x140
Fabric consumption	m	3.0 (h1.40)



## Product description

Seat and backrest structure	Made of rigid, self-supporting, standard BIO 7% polyurethane with the metal bushings necessary to hook it to the base inserted. Polyurethane <b>BIO 20%</b> available upon request. The channels needed for stitching fabric or leather are provided.
Seat and backrest padding	Made of flexible, SUPER SOFT polyurethane, molded density 60 Kg\cbm, available both <i>Traditional Flexible</i> and <b>RECYCLED</b> at 64%.
Base	Swivel aluminum base - 4 spokes, gas lift
Fire resistance classes of padding	Depending on the type of polyurethane chosen, the following certifications are available: <ul style="list-style-type: none"> <li>• class 1IM (Italy)</li> <li>• TB 117 (USA)</li> <li>• British standard (UK)</li> <li>• M4 (French)</li> </ul>
Disassembled body size	0.48 cbm
Packaging on box 120x78h72 (2 seats + 2 seatbacks)	0.70 cbm (2 seats + 2 seatbacks)
Basic dimensions (cubic meters)	0.03 cbm
Mechanical resistance test	Complies with the strength, durability and safety requirements of 1 <sup>st</sup> level of EN 16139:2013+AC:2013

## USE AND MAINTENANCE

Use in indoor environments such as waiting rooms, conference rooms, hotels and restaurants.

Do not use substances containing solvents or abrasives.

At the end of its life separate the various components and, when impossible to reuse, dispose of them following the rules of the place.

The following form is drawn up according to law 126\91 and DL101\97